

Microchip Technology

C | T | 532

GLAUCOMA

THERAPY

FOR

**MAXIMUM** 

DEMANDS

LASER...INNOVATION
MADE IN GERMANY

www.arclaser.de info@arclaser.de

# C | T 532

Modern laser architecture at the "speed of light"

Microchip Technology CITO 532

# CITO 532 NO COMPROMISES.



Designed for the anterior segment

Highest repetition rate

Homogeneous spot quality

Highest pulse-to pulse stability: unique in OPHTHALMOLOGY

Secure compartment for all cable connections Anti-collision system for tall patients

Electronic heightadjustment up to 920 mm with 2 height adjustable lifts

Stable and slim design, wheelchair accessible

# Spacious legroom

920 mm

580 mm

The compact system combines laser, table and slit lamp - wheels are available upon request.

725 mm

# THE MODERN SLT

Homogeneous spot quality for optimal reproducibility









## The perfect optic for the anterior eye segment







Designed for the anterior segment





CITO 532 SLT Laser






THE SLT LASER TREATMENT STIMULATES THE TRABECULAR MESHWORK IN A SPECIFIC WAY AND GENERATES A SIGNIFICANT REDUCTION OF INTRAOCULAR PRESSURE (IOP) IN A NATURAL WAY







The laser beam activates the trabecular meshwork. The ideal treatment is done with an angle of 180° per session.

### The most homogeneous spot in A.R.C. Laser history

Regards to the quality of our laser spot, this beam stands out in terms of reliability and stability compared to the predecessor TRABECULAS.

Thanks to the microchip architecture with its quick refresh and stable laser specifications, you and your patients could benefit from a better reproducibility and predictability of the procedure.



World's fastest SLT

Argon-KTP: small and portable

**Nd:YAG with DualSpot** 





# **MORE OPTIONS: VARIO.**

2 high-class lasers on one table.

\* Picture is an example

### **SPECIFICATIONS**

SLT-LASER CITO 532 GEN II

| Laser Wavelength                             | Q-switched, Nd:YAG<br>frequency doubled 532 nm                                    |
|--|---|
| Output Energy (Laser)                        | 2 mJ max.   |
| Therapy beam pulse settings                  | 0.1 mJ steps from 0,2 to 1,4 mJ<br>0.2 mJ steps to 2 mJ                           |
| Beam Delivery                                | Coupling in slit lamp   |
| Display / Control                            | 7" Color touch screen   |
| Cooling                                      | Internal, air   |
| Aiming Beam                                  | 635 nm red < 1mW, adjustable  |
| Power Requirement                            | 100-240 V AC, 47-63 Hz , 5A   |
| Weight / Dimensions with table and slit lamp | 53 kg<br>HWD <99 cm / 100 cm / 58 cm  |
| Laser classification<br>EN 60825-1           | <b>Therapy beam:</b> 3B   532 nm, E = 2,5 mJ<br>Aiming beam: 2   635 nm, P < 5 mW |

Alterations of the described features or pictured features are possible. Please keep updated on the current status before ordering.

Subject to change without notice.  $\ensuremath{\texttt{@}}$  A.R.C. Laser 2018.



VISIBLE AND INVISIBLE LASER RADIATION
Avoid direct irradiation of eye or skin or scattered radiation.
Laser class: see table at the left



Your local distributor:



A.R.C. Laser GmbH Bessemerstr. 14 90411 Nuremberg Germany +49 911 217 79-0
 +49 911 217 79 99
 info@arclaser.com

www.arclaser.com